



ARDON®
WORKWEAR
& **OUTDOOR**

ARDON® DIGGER O1

WORKING SHOES



TECHNICAL SHEET



DRY AIR



DEFUSE CONTROL



NONMETALLIC



REFLECTIVE



ARDON[®]
WORKWEAR
 & **OUTDOOR**

ARDON[®] DIGGER 01

WORKING SHOES

ARTICLE G3239

MATERIAL

Upper MICROFIBER / CANVAS type fabrics
 Lining MESH laminated breathable fabric
 Sole MD/rubber/TPU, glued technology
 Toe cap -
 Plate -
 Insole ANATOMIC FOAM anatomically shaped EVA foam

SIZE

36-48

UNIT

pair

PACKAGE

Units in a carton 10 pairs

Units in a box 1 pair

DIMENSIONS

	36-43	44-48	
Carton H x W x D (cm)	34 x 48.5 x 63	37 x 52.5 x 63	
Carton (cbm)	0,104	0,122	

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	238	244	251	258	264	271	278	284	291	298	304	311	318	-	-	-
Foot length cm	-	23,3	23,9	24,6	25,3	25,9	26,6	27,3	27,9	28,6	29,3	29,9	30,6	31,3	-	-	-

DESCRIPTION

Low shoes in sports design. Breathable upper is made of solid fabric and microfiber, the toe cap is reinforced with PU. Wearing comfort is increased by padding the tongue and the area around the heel and ankle, but mainly the shoes are equipped with an anatomically shaped insole, made of a material that effectively dampens the impact of the tread and ensures comfort even during long-term wear. The sole made of a combination of MD / rubber / TPU material ensures a soft tread and at the same time provides the highest level of anti-slip properties.

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

NORMS

(EU) 2016/425

EN ISO 20347:2012 Personal protective equipment – Occupational footwear

Category O1 SRC

Categories	EN ISO 20347	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection		
P - resistance to punctures (protective insole)		
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heat up to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts	✓	
-		
-		
-		

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3239/36	8592390157331	9.70	0.970
G3239/37	8592390157348	9.80	0.980
G3239/38	8592390157355	10.10	1.101
G3239/39	8592390095077	10.20	1.020
G3239/40	8592390095084	10.50	1.050
G3239/41	8592390095091	10.80	1.080
G3239/42	8592390095107	11.20	1.120
G3239/43	8592390095114	11.40	1.140
G3239/44	8592390095121	11.75	1.175
G3239/45	8592390095138	12.10	1.210
G3239/46	8592390095145	12.30	1.230
G3239/47	8592390157362	12.80	1.280
G3239/48	8592390157379	13.30	1.330





ARDON®

**WORKWEAR
& OUTDOOR**





ARDON®

**WORKWEAR
& OUTDOOR**



TECHNICAL SHEET