

## TECHNICAL DATA SHEET

### G6000


#### Eye protection

Article NO: E4053


Lens: clear  
 Material- lens: polycarbonate  
 Material- frame: polypropylene



Goggles of innovative solution. Visor is panoramatic with excellent wide field. The rubber band is adjustable and 25 mm wide. The nose bridge is soft and provides excellent comfort. Goggles are very light and flexible. Clear visor is anti-fogging and anti-scratching, protects against UV radiation and it is resistant to low-energy shocks (up to 45 m/s) at extreme temperatures (-5 °C - +55 °C).



Adjustable temple length - NO



Adjustable temple angle - NO



Anti-fogging lens - YES



Anti-scratching lens - YES

#### Clear lens, 2-1.2 1 FT 0

Type of the filter:	2	UV filter
Shade number:	1.2	clear lens
Optical class:	1	permanent use
Mechanical resistance:	FT	resistant to low-energy shocks at extreme temperatures
Type of the lens:	0	original lens



---

This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001: Personal eye protection. General requirements.

EN 170:2002: Personal eye-protection - Ultraviolet filters - Transmittance requirements and recommended use.

Certified by Notified body no. 2797 (BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands),  
Certificate no CE 749754, dated 26<sup>th</sup> August 2021.

---

Pieces in carton:	250
Pieces in box:	10
Polybag packing (pieces):	1
Carton weight:	10 kg
Carton size:	0,095 m <sup>3</sup>

---

Store in dry and dark environment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents.

It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.

---