

■ Application:

- It prevents fogging the mirror



ELECTRICAL SPECIFICATION

MODEL	3020	4030	6040	8050
Size	30 cm * 20 cm	40 cm * 30 cm	60 cm * 40 cm	80 cm * 50 cm
Input Voltage	230V / 50Hz			
Input Power	1.5 ÷ 2.5W/dm ²			
Power	9 ÷ 15W	18 ÷ 30W	36 ÷ 60W	60 ÷ 100W
Averaged power consumption	10.93W	29.41W	38.59W	74.53W
Average value of temperatura rising	10°C ÷ 20°C			
Wire	OMYp 2x0.5mm ² (2x20AWG)			
Wire lenght	1,5mb			
Material	PET (Dupont)			
Heating surface	0,06 m ²	0,12 m ²	0,24 m ²	0,40 m ²
Thickness	3mm			
Evaporation time	Od 1 do 10 min			
Sticking strength	0.5kg/cm ²			
Softening	180°C			
Hot melting temperature is over	260°C			
Warranty	2 years			

WORKING ENVIRONMENT

Working Temperature	-25°C ÷ 60°C
Working Humidity	10 ÷ 90% RH non-condensing
Storage Temperature and Humidity	-20°C ÷ 85°C, 5 ÷ 90% RH non-condensing
Degree of IP protection	IP54