



ARDON[®]
WORKWEAR
& **OUTDOOR**

ARDON[®] SOFTEX S1P

SAFETY SHOES



DRY AIR



DEFUSE
CONTROL



WASH-FRIENDLY

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® SOFTEX S1P

SAFETY SHOES

ARTICLE	G3352	G3366	
COLOUR	black/yellow	black/blue	
MATERIAL	textilie tytu SOFTSHELL		
Upper	MESH laminated breathable fabric		
Lining	PU/PU, two-component spray coating, oil resistant, anti-static, antislip		
Sole	steel 604		
Toe cap	steel		
Plate	ANATOMIC GEL - anatomically shaped from PU foam with a gel cushioning in the heel area		
Insole			
SIZE	38-50	38-50	
UNIT	pair		
PACKAGE			
Units in a carton	10 pairs		
Units in a box	1 pair		
DIMENSIONS			
	38-41	42-45	46-50
Carton H x W x D (cm)	57x 33 x 38,5	59,5x 35,5 x 40,5	62x38x41,5
Carton (cbm)	0,0724	0,0855	0,0978



TECHNICAL SHEET

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	-	-	248	255	262	270	276	283	290	297	304	310	317	323	330	-
Foot length cm	-	-	-	24,3	25,0	25,7	26,5	27,1	28,3	28,5	29,2	29,9	30,5	31,2	31,8	32,5	-

DESCRIPTION

Safety softshell low shoe in sporty design. The ANATOMICGEL insole with a cushioning gel element in the heel takes care of the increased comfort of the shoes. The shoes are equipped with a steel toe and an anti-puncture insole. The stable polyurethane sole made by direct spraying provides the highest level of anti-slip properties.



ARDON[®]
WORKWEAR
 & **OUTDOOR**

NORMS

(EU) 2016/425

EN ISO 20345:2011

Category

Personal protective equipment – Safety footwear

S1P SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3352/38	8592390132376	12.3	1.23
G3352/39	8592390132383	12.6	1.26
G3352/40	8592390132390	12.8	1.28
G3352/41	8592390132406	13.1	1.31
G3352/42	8592390132413	13.5	1.35
G3352/43	8592390132420	14.0	1.40
G3352/44	8592390132437	14.5	1.45
G3352/45	8592390132444	15.0	1.50
G3352/46	8592390132451	15.7	1.57
G3352/47	8592390132468	16.2	1.62
G3352/48	8592390132475	16.7	1.67
G3352/49	8592390132482	17.1	1.71
G3352/50	8592390132499	17.8	1.78
G3366/38	8592390152442	12.3	1.23
G3366/39	8592390152459	12.6	1.26
G3366/40	8592390152466	12.8	1.28
G3366/41	8592390152473	13.1	1.31
G3366/42	8592390152480	13.5	1.35
G3366/43	8592390152497	14.0	1.40
G3366/44	8592390152503	14.5	1.45
G3366/45	8592390152510	15.0	1.50
G3366/46	8592390152527	15.7	1.57
G3366/47	8592390152534	16.2	1.62
G3366/48	8592390152541	16.7	1.67
G3366/49	8592390152558	17.1	1.71
G3366/50	8592390152565	17.8	1.78



ARDON[®]
WORKWEAR
& OUTDOOR





ARDON®

**WORKWEAR
& OUTDOOR**



TECHNICAL SHEET