

article#	e325-foa
article description	eMobility Charging socket outlet Type 2 w/o actuator (front panel mount) IP44/54
description long	Infrastructure surface-mounted flange socket Type2 for charging electric vehicles (EV) with alternating current (AC) consisting of: surface mounted socket type2 (AC 32A), contacts: screw connection, brass nickel-plated frame with self-closing hinged lid intermediate flange (front panel mounting) flange gasket mounting screws Protection rating: IP44/54
GTIN (EAN)	9003399584459
country of origin	AT
customs number	85366990
net weight	0.311 kg
packaging quantity	1
minimum order quantity	1

ETIM 9.0	EC002898
Model	Charging socket outlet
Standard	Type 2
Connection system	Screw connection
With interlocking actuator	False
With access interlocking	False
Degree of protection (IP)	Other
Width	85 mm
Height	92 mm
Depth	86 mm
Nominal voltage	480 V
Max. nominal current	32 A
Type of current	AC 3-phase
Number of communication contacts	2
Cross section of the power contacts	2.5 – 6 mm ²
Contact material	CuZn
Surface treatment contacts	Nickel-plated

wire flexible	2,5-6 mm ²
contact screws	120 (L1-L3,N,PE) / 80 (CP,PP) Ncm
stripping length	15 (PE) / 12 (L1-L3,N) / 10 (CP,PP) mm

