



ARDON®
WORKWEAR
& OUTDOOR

ARDON® DERRICK S3

SAFETY SHOES



DRY AIR



DEFUSE CONTROL



NONMETALLIC



WATER REPELLENT



FLAT ANTI-SLIP

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® DERRICK S3

SAFETY SHOES

ARTICLE G3160

MATERIAL

Upper
 Lining
 Sole

ACTION NUBUK – cowhide leather with polyurethane / textile
 MESH laminated breathable fabric
 rubber, oil resistant, antistatic, anti-slip, glued technology

Toe cap
 Plate
 Insole

composite 459
 kevlar

ANATOMIC FOAM anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area

SIZE

39-48

UNIT

pair

PACKAGE

Units in a carton

10 pairs

Units in a box

1 pair

DIMENSIONS

Carton H x W x D
 (cm)

39-42	43-48
32.5 x 43.5 x 59.5	37.5 x 45.5 x 64.5

Carton (cbm)

0,084	0,110
-------	-------

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	-	-	-	256	263	269	276	283	289	296	303	309	316	-	-	-
Foot length cm	-	-	-	-	25,1	25,8	26,4	27,1	27,8	28,4	29,1	29,8	30,4	31,1	-	-	-

DESCRIPTION

Safety shoe in modern street design. The upper of the shoe is made of action NUBUK material with a waterproof finish, the tongue and ankle area is made of a fabric that provides higher breathability.

The shoes are equipped with a composite toe and a flexible Kevlar insole against puncture. The stable flat sole made of rubber provides the highest level of anti-slip properties.

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S3 SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts	✓	
-		
-		
-		

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3160/39	8592390068521	13.26	1.326
G3160/40	8592390068538	13.76	1.376
G3160/41	8592390068545	14.26	1.426
G3160/42	8592390068552	14.76	1.476
G3160/43	8592390068569	16.37	1.637
G3160/44	8592390068576	16.87	1.687
G3160/45	8592390068583	17.37	1.737
G3160/46	8592390068590	17.87	1.787
G3160/47	8592390068606	18.37	1.837
G3160/48	8592390068613	18.87	1.887



ARDON®
WORKWEAR
& OUTDOOR





ARDON®

**WORKWEAR
& OUTDOOR**



TECHNICAL SHEET