



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® DERRICK HIGH S3

SAFETY SHOES



TECHNICAL SHEET



**DRY AIR**



**DEFUSE CONTROL**



**NONMETALLIC**



**WATER REPELLENT**



**FLAT ANTI-SLIP**



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® DERRICK HIGH S3

SAFETY SHOES

**ARTICLE** G3187

**MATERIAL**

Upper  
 Lining  
 Sole

ACTION NUBUK – cowhide leather with polyurethane / textile  
 MESH laminated breathable fabric  
 rubber, oil resistant, antistatic, anti-slip, glued technology

Toe cap  
 Plate  
 Insole

composite 459  
 kevlar

ANATOMIC FOAM anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area

**SIZE**

39-48

**UNIT**

pair

**PACKAGE**

Units in a carton

10 pairs

Units in a box

1 pair

**DIMENSIONS**

Carton H x W x D  
 (cm)

39-42  
 33.5 x 53 x 59.5

43-48  
 38 x 57 x 64.5

Carton (cbm)

0,106

0,140

Size EUR

35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Insole length mm

-	-	-	-	256	263	269	276	283	289	296	303	309	316	-	-	-
---	---	---	---	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	---	---	---

Foot length cm

-	-	-	-	24,6	25,3	25,9	26,6	27,3	27,9	28,6	29,3	29,9	30,6	-	-	-
---	---	---	---	------	------	------	------	------	------	------	------	------	------	---	---	---

**DESCRIPTION**

Safety shoe in modern street design. The upper of the shoe is made of action NUBUK material with a waterproof finish, the tongue and ankle area is made of a fabric that provides higher breathability.

The shoes are equipped with a composite toe and a flexible Kevlar insole against puncture. The stable flat sole made of rubber provides the highest level of anti-slip properties.

TECHNICAL SHEET



**ARDON**<sup>®</sup>  
**WORKWEAR**  
 & **OUTDOOR**

## NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S3 SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts	✓	
-		
-		
-		

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

<b>CODE</b>	<b>EAN</b>	<b>CARTON WEIGHT (KG)</b>	<b>UNIT WEIGHT (KG)</b>
G3187/39	8592390073716	14.82	1.482
G3187/40	8592390073723	15.62	1.562
G3187/41	8592390073730	16.22	1.622
G3187/42	8592390073747	16.50	1.650
G3187/43	8592390073754	17.22	1.722
G3187/44	8592390073761	17.64	1.764
G3187/45	8592390073778	18.55	1.855
G3187/46	8592390073785	19.05	1.905
G3187/47	8592390073792	19.44	1.944
G3187/48	8592390073808	19.94	1.994



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**





**ARDON®**

**WORKWEAR  
& OUTDOOR**



TECHNICAL SHEET