



# O'SPA

## The ultra-versatile spa heat pump

The ultra-compact Poollex O'Spa is a spa heat pump that saves up to 75% energy on spa heating compared with a conventional electric heater (for the same power output). The O'Spa can be installed on any type of spa or Nordic bath and can take over from the existing electric heater to optimise your spa's temperature rise.

- **Ideal for warm and temperate climates:** Optimised for maximum performance in warm and mild conditions.
- **Reversible hot / cold :** For water that's always at the ideal temperature.
- **Control via Wifi connection :** Programme your spa sessions remotely.
- **Compatible with all spas:** Optional Plug & Play connection kit.
- **Integrated control of an auxiliary circulation pump (optional relay)**
- **Integrated control of spa heater (relay supplied)**

	3 kW	5 kW	7 kW
Climate	Hot	Temperate	

**+**  
INTEGRATED CHILLER  
FUNCTION DOWN TO 3°C



**POOLEX**  
Application

App Store

Google Play



Compatible with all treatments



Integrated WiFi

### GUARANTEES

- Heat pump **2 YEARS**
- Compressor **5 YEARS**
- Titanium coil (corrosion resistant) **10 YEARS**

O'SPA		3 kW	5 kW	7 kW
Recommended climate		Hot	Temperate	
Reference : PC-OSPA		30	50	70
Air 26°C Water 26°C 80% hygro	Capacity (kW)	3	5	7
	Power consumption (kW)	0,58	0,97	1,35
	COP	5,15	5,20	5,20
Air 15°C Water 38°C Hygro 70%	Capacity (kW)	1,80	3,30	5,00
	Power consumption (kW)	0,65	1,10	1,23
	COP	2,77	3	4,05
Air 26°C Water 38°C Hygro 80%	Capacity (kW)	2,80	4,6	6,3
	Power consumption (kW)	0,72	1,09	1,5
	COP	4,01	4,05	4,05
Air 35°C Water 27°C Hygro 70%	Capacity (kW)	1,46	2,99	3,50
	Power consumption (kW)	0,53	1	1,18
	EER	2,75	2,99	2,97
Air 15°C Water 5°C Hygro 70%	Capacity (kW)	0,9	1,80	1,4
	Power consumption (kW)	0,47	0,75	1
	EER	1,9	2,4	1,3
Power supply	Mono 220-240V / 50Hz			
Connections	32 / 38mm			
Max power (kW)	0,7	1,35	2,00	
Max current (A)	3,11	5,99	8,87	
Heating temperature range	10°C / 40°C			
Cooling range	8°C / 28°C			
Operating range	-15°C~43°C			
Flow rate (m³/h)	1,3	2,16	2,16	
Refrigerant	R32 / 0,24 kg	R32 / 0,40 kg	R32 / 0,45 kg	
Packaging dimensions (mm)	470x400x438		657x460x490	
Dimensions (mm)	440x350x430		600x430x430	
Net / gross weight (kg)	26 / 28	32 / 35	30 / 35	
Noise level at 1 m (dB(A))	< 50	< 53	< 50	
Noise at 4 m (dB(A))	< 38	< 40	< 38	
Noise level at 10 m (dB(A))	< 30	< 32	< 30	
Compressor type	Rotary			
Exchanger	Twisted Tech® Titanio			
Function	Heating + Cooling (Chiller)			
Pressure drop (mCE)	1,2	1,2	1,2	

CHILLER

## DUAL FUNCTION

O'Spa is the essential choice for wellness enthusiasts, offering a dual function: heating and cooling.

**The heating function increases the water temperature, saving up to 75% energy compared with a conventional electric heater.**

The O'Spa can be fitted to all types of spa and Nordic bath, optimising the temperature rise of your spa for optimum comfort and experience. This unique dual function makes the O'Spa a high-performance, versatile piece of equipment that meets the demanding needs of users, whatever their environment.

**The Chiller function cools the water efficiently, providing a refreshing bathing experience by reducing the temperature by up to 3°C.**

Ice bath therapy is increasingly recognised as a way of harnessing the body's natural recuperative powers.

## THE BENEFITS OF A CHILLER :

- Improved blood circulation
- Reduced arterial hypertension
- Strengthens the immune system
- Muscle recovery and relaxation
- Reduced stress

## COMPACT DIMENSIONS :



## Accessories included



Remote touch screen (optional)



Hydraulic connection kit (optional)



Pilot relay (included)



Circulation pump relay (optional)



Differential socket with 5m cable



Hydraulic fittings (2 sets)



Clamps (2 sets)