



ARDON[®]
WORKWEAR
& OUTDOOR

ARDON[®] GRINDER 02

WORKING SHOES



TECHNICAL SHEET



DRY AIR



**DEFUSE
CONTROL**



**WATER
REPELLENT**



ARDON®
WORKWEAR
& OUTDOOR

ARDON® GRINDER O2

WORKING SHOES

ARTICLE G3326

MATERIAL

Upper ACTION NUBUK – cowhide leather with polyurethane / fabric coating
 Lining MESH laminated breathable fabric
 Sole PU/rubber, two-component spray coating, oil resistant, anti-static, antislip, resistant up to 300 °C

Insole ANATOMIC FOAM anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area

SIZE

36-48

UNIT

pair

PACKAGE

Units in a carton 10 pairs

Units in a box 1 pair

DIMENSIONS

Carton H x W x D (cm)

36-39
31.5 x 45.5 x 61.5

40-43
33.5 x 47.5 x 61.5

44-48
37 x 49.5 x 64

Carton (cbm)

0,0881

0,0979

0,117

Size EUR

35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Insole length mm

-	237	243	250	257	263	270	277	283	290	297	303	310	317	-	-	-
---	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	---	---	---

Foot length cm

-	22,7	23,3	24,0	24,7	25,3	26,0	26,7	27,3	28,0	28,7	29,3	30,0	30,7	-	-	-
---	------	------	------	------	------	------	------	------	------	------	------	------	------	---	---	---

DESCRIPTION

Working ankle boot with upper made of ACTION NUBUK material - cowhide leather with polyurethane coating. The wide PU / rubber sole has SRC anti-slip properties and is resistant to contact heat up to 300 ° C. The ANATOMIC FOAM insole ensures increased comfort of the shoes.

TECHNICAL SHEET



ARDON[®]
WORKWEAR
& OUTDOOR

NORMS

(EU) 2016/425

EN ISO 20347:2012 Personal protective equipment – Occupational footwear

Category O2 HRO SRC

Categories	EN ISO 20347	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection		
P - resistance to punctures (protective insole)		
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C	✓	
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		

TECHNICAL SHEET



ARDON®

**WORKWEAR
& OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3326/36	8592390125385	12.80	1.280
G3326/37	8592390125392	13.20	1.320
G3326/38	8592390125408	13.60	1.360
G3326/39	8592390125415	14.10	1.410
G3326/40	8592390125422	14.60	1.460
G3326/41	8592390125439	15.00	1.500
G3326/42	8592390125446	15.30	1.530
G3326/43	8592390125453	15.80	1.580
G3326/44	8592390125460	16.30	1.630
G3326/45	8592390125477	16.80	1.680
G3326/46	8592390125484	17.50	1.750
G3326/47	8592390125491	18.00	1.800
G3326/48	8592390125507	18.50	1.850



ARDON®
WORKWEAR
& OUTDOOR





ARDON®

**WORKWEAR
& OUTDOOR**



TECHNICAL SHEET