

GENALEX GOLD LION CUSTOM TUBE B749/ECC82/12AU7

pin #	Electrode name
1	Plate of 2 nd triode
2	Grid of 2 nd triode
3	Cathode of 2 nd triode
4,5,9	Heater
6	Plate of 1 st triode
7	Grid of 1 st triode
8	Cathode of 1 st triode

Electrical data of new tube

		Comment
Grid reverse current, μA , not more	0.2	3, 4
Heater current, mA not less	275	1
	135	2
	325	1
	160	2
Plate current, mA not less	7.8	3, 5
	13.0	
Plate current at the beginning of the curve, μA not more	10	3, 6
Transconductance, mA/V, not less	1.75	3, 5
Amplification factor, not less	13	3.5

Comments:

1. Plate voltage 6.3v
2. Heater voltage 12.6v
3. Heater voltage 6.3v or 12.6v
4. Plate voltage 250v, grid voltage -8.5v, grid circuit resistance 0,25M Ω m
5. Plate voltage 250v, grid voltage -8.5v
6. Plate voltage 250v, grid voltage -24v

Electrical parameters that could be changed within exploitation

Transconductance, ma/v, not less	1.3
Grid reverse current, μA , not more	0.5

Limited values

Heater voltage, V, not less	6.0 or 12.0	
	not more	6.6 or 13.2
Plate voltage, V, not more	300	
Cathode to heater voltage:		
Positive, V, not more	200	
Negative, V not more	200	
Plate current, mA not more	22	
Plate dissipation power of each triode, W, not more	2.75	
Each triode grid circuit resistance:		
under fixed bias, Mohm, not more	0.25	
under automatic bias, Mohm not more	1.0	
Plate voltage of cold tube, V, not more	600	
Max grid reverse current, V, not more	55	

The tube can't be exploited at two or more limited conditions.

Interelectrode capacitances:

Input capacitance of each triode, pf, nominal	1.6
Output capacitance of each triode, pf, nominal	0.5
Transfer capacitance of each triode, pf, nominal	1.5